



DC-UPS

NBPAQ33G1***

1 Short description

The battery-buffered DC power supply of the AKKUTEC series operates according to the standby parallel principle and, in conjunction with a lead accumulator, ensures that the DC voltage supply is safely maintained in the event of a power failure. The buffer time depends on the charge state of the accumulator and the discharge current

The power supply has the following characteristics:

- Battery charger with I/U-charging characteristics
- Micro controller-supported battery management
- Temperature tracking of the charge voltage by external sensor module (option)

2 Technical Data

Input	
Input voltage	230 V AC $\pm 15\%$ 196...265 V AC)
Frequency	47...63 Hz
Input current	0,7 A @ 230 V AC
Inrush current	≤ 30 A/2 ms
Nominal input power	86 W @ (U _e = 230 V AC, U _a = 26,8 V DC, I _a = 2,8 A)
Output	
Nominal output voltage	24 V DC
Output voltage (without temperature tracking)	19,8...26,8 V DC $\pm 0,4\%$
Output voltage (with temperature tracking)	19,8...27,8 V DC $\pm 0,4\%$
Final charging voltage (with/without temperature tracking)	26,8 V DC $\pm 0,4\%$ / 26,8...27,8 V DC $\pm 0,4\%$
Load shedding	19,8 V DC $\pm 0,4\%$
Nominal output current	2,8 A
Self consumption current (in back-up operation)	70 mA
Max power loss "worst case"	12 W @ (U _e = 230 V AC, U _a = 26,8 V DC, I _a = 2,8 A)
Efficiency	86,3 % @ (U _e = 230 V AC, U _a = 26,8 V DC, I _a = 2,8 A)
Charging characteristics	IU-characteristics DIN 41773-1
Fusing	
Fusing battery circuit (external)	3 A (T), 250 V
Fusing output (external)	3 A (T), 250 V
Pre-fusing	5 A (T), 250 V
In General	
Protective system housing	IP20
Overvoltage category	II
Degree of pollution	2

Document

page 1 / 2

Q33G1M10D02_AKKUTEC_2403_220118 Original language: German

J. Schneider Elektrotechnik GmbH

Helmholtzstraße 13, 77652 Offenburg · Postfach 2327, 77613 Offenburg · Werner-von-Siemens-Straße 12, 77656 Offenburg
Tel +49 (0) 781 206 0 · Fax +49 (0) 781 253 18 · info@j-schneider.de · www.j-schneider.de · Amtsgericht Freiburg HRB 470458
Geschäftsführer: Dipl.-Betriebswirtin (BA) Bettina Schneider · Dipl.-Wirt.-Ing. (FH) Rolf Anti · UST-Ident-Nr. DE142532740

Technical Datasheet

AKKUTEK 2403



J. Schneider
Elektrotechnik

Battery type	Lead accumulator*
dimensions (H x S x D) standard unit	92,5 mm x 60 mm x 116 mm
weight standard unit (without batteries)	0,6 kg
Operational temperature	0 °C ... +45 °C
Operational temperature (UL tested)	+10 °C ... +50 °C
Storage temperature	0 °C ... +50 °C
Relative humidity	≤95 % non-condensing
Max. height above sea level (without power reduction)	2000 m

3 Norms and regulations

Power HF transformer to ensure safe separation of primary and secondary	EN 61558-2-16, fulfills SELV / PELV
Optocoupler to ensure safe isolation primary/secondary	EN 60747-5-1, fulfills SELV / PELV
Ermitted interference EN 61000-6-4	EN 61000-3-2 and EN 61000-3-3 class A EN 55011 class B
Interference immunity: EN 61000-6-2	EN 61000-4-2 EN 61000-4-3 EN 61000-4-4 EN 61000-4-5 EN 61000-4-6 EN 61000-4-11 (voltage drops)
Total unit	EN 62368-1 EN 61010-1 / EN 61010-201