



DC-UPS

VCP20727G02051

1 Short description

The buffered DC power supply of the **C-TEC** of series is an open frame device, a board, which includes ultra-capacitors as energy storage inside the housing. During normal operation this capacitor is charged from the system voltage (U_e). The connected DC consumers are supplied as well from the system voltage. In case of an interruption of the system voltage, the energy of the ultra-capacitor is released regulated. With a dc/dc converter the load is supplied from the capacitor until it is discharged. The backup time depends on the state of charge of the capacitor and the discharge current.

The power supply has the following characteristics:

- Maintenance-free because of long-life ultra-capacitors
- Mikrocontroller based charging and discharging of the ultra-capacitors
- Control of operation and status of charge with potential-free contacts and LED
- Capacity extension possible with external capacitor extension modules

2 Technical Data

Nominal input voltage	24 V DC -15 % / 10 %
Input voltage range	20,4 V ... 26,4 V DC
Min. charging voltage	23,7 V DC
Nominal input current (at 24,0 V DC) C charged 3 A load	3,1 A DC
Output voltage in back-up operation	23,0 V DC ± 2 %
Max. nominal output current	3 A DC (at 0,94 kJ)
Nominal output current at maximum energy	2 A DC (at 1,0 kJ)
Current limitation	1,05 ... 1,2 x I_{Nenn}
Power loss at $U_c >$	2,5 W
power loss at 100% load and charging	7 W (max 60 seconds)
Efficiency at $U_c >$	>96% @ ($U_e=24,0$ V DC; $U_a=22,9$ V DC; $I_a=I_{Nenn}$)
Internal device protection (internal)	4 A (T)
Fuse DC-output circuit (external)	3 A (T)
Type of connection: input U_e	Spring terminal max. 1,0 mm ²
Type of connection: output U_a	Spring terminal max. 1,0 mm ²
Type of connection: message contact	Spring terminal max. 1,0 mm ²
Max. load message contact (U_e -OK ¹)	30 V / 0,5 A potentialfree relay contact

¹ The message contacts are coupled with the LED display. The illumination of a LED effects the activation of the corresponding relay.

Technical Datasheet

C-TEC 2403-1



J. Schneider
Elektrotechnik

Protective system	IP20 a. EN 60529
Environmental temperature	-20 °C ... 60 °C
Storage temperature	-20 °C ... 60 °C
Rel. humidity	≤95% condensation not permissible
Max. mounting height (without load reduction)	2000 m above sea level
dimensions (HxWxd)	110 mm, 90 mm, 45 mm
weight	0,3 Kg

3 Norms and regulations

Terminal voltage	SELV / PELV according to EN 60950 EN 50178
Ermited interference	EN 6100-3-2 EN 6100-3-3 class A EN 55011 class B EN 62040 -2
Noise immunity	EN 61000-6-2 EN 62040-2 EN 61000-4-2 (Static discharge ESD) 8kV/6kV EN 61000-4-3 (electromagnetic fields) 10V/m 27 – 1000MHz 3V/m 1400 - 2700MHz EN 61000-4-4 (fast transients / Burst) DC IN, DC OUT 2kV others 1kV EN 61000-4-5 (Stoßstrombelastung / Surge) DC IN 0.5kV EN 61000-4-6 (conducted noise immunity) 10V 150kHz – 80MHz EN 61000-4-11 (voltage interruptions) back-up with ultra capacitors
Total unit	EN 50178 EN 60950 UL 508