



## DC-UPS

### NCPA0727G10002

### 1 Short description

The DC-UPS of the series C-TEC includes ultra-capacitors as energy storage inside the housing. This capacitor is charged with the system voltage ( $U_e$ ) during normal operation. The connected loads are supplied as well from the system voltage. In case of an interruption of the system voltage the energy of the ultra-capacitors is released in a regulated way. With a dc dc converter, the load is supplied by the capacitor until it is discharged. The back-up time depends on the state of charge of the capacitors and on the discharge current.

The DC-UPS has the following characteristics:

- Maintenance-free because of long-life ultra-capacitors
- Microcontroller based charging and discharging of the ultra-capacitors
- Control of operation and status of charge with potential-free contacts and LED
- $U_e$  o.k. message via potential-free relay contact
- Capacity extension possible with external capacitor extension modules (CEM)

### 2 Technical Data

Nominal input voltage	12 V DC -15 % / 10 %
Input voltage range	10,2 V ... 13,2 V DC
Min. charging voltage	11,8 V DC
Nominal input current (at 24,0 V DC) C charged 3 A load	3,1 A DC
Output voltage in back-up operation	11,5 V DC $\pm$ 2 %
Nominal output current Max	3 A DC (at 0,94 kJ)
Nominal output current at maximum energy	2 A DC (at 1,0 kJ)
Current limitation	1,05 ... 1,2 x $I_{Nom}$
Power loss at $U_c >$	2,5 W
Power loss at 100 % load and charge	7 W (max. 60 seconds)
Efficiency at $U_c >$	>96% @ ( $U_e=12,0$ V DC; $U_a=11,5$ V DC; $I_a=I_{Nom}$ )
Internal device protection (internal)	4 A (T)
fusing DC-output circuit (external)	3 A (T)
Type of connection: input $U_e$	Spring terminal max. 1,0 mm <sup>2</sup>
Type of connection: output $U_a$	Spring terminal max. 1,0 mm <sup>2</sup>
Type of connection: message contacts	Spring terminal max. 1,0 mm <sup>2</sup>
Max. load message contact ( $U_e$ -OK <sup>1</sup> )	30 V / 0,5 A potential-free relay-contact
Protective system	IP20 u. EN 60529
Operational temperature	-20 °C ... 60 °C
Storage temperature	-20 °C ... 60 °C
Rel. humidity	$\leq$ 95% no condensation

<sup>1</sup> The message contacts are coupled with LED display. (see section 4.1). The illumination of a LED effects the activation of the corresponding relay.

# Technical Datasheet

## C-TEC 1203-1



**J. Schneider**  
**Elektrotechnik**

Max. mounting height (without load reduction)	2000 m above sea level
dimensions (HxWxD)	92,5 mm, 60 mm, 116 mm
weight	0,6 Kg

### 3 Norms and regulations

Terminal voltage	SELV / PELV according to EN 60950 EN 50178
Ermited interference	EN 6100-3-2 EN 6100-3-3 class A EN 55011 class B EN 62040 -2
Noise immunity	EN 61000-6-2 EN 62040-2  EN 61000-4-2 (Static discharge ESD) 8kV/6kV EN 61000-4-3 (electromagnetic fields) 10V/m 27 – 1000MHz 3V/m 1400 - 2700MHz EN 61000-4-4 (fast transients / Burst) DC IN, DC OUT 2kV others 1kV EN 61000-4-5 (Stoßstrombelastung / Surge) DC IN 0.5kV EN 61000-4-6 (conducted noise immunity) 10V 150kHz – 80MHz EN 61000-4-11 (voltage interruptions) back-up with ultra capacitors
Total unit	EN 50178 EN 60950