



Switch mode power supply

NFPG 1529G02001
(TRETEC 2412 N)

1 Short description

The **TRETEC 2412 N** is a switch mode power supply of the latest generation, which is characterised by its high efficiency and the resulting minimum power losses. The device also works with power boost function (output $15\text{ A} \leq 5\text{ seconds}$ at 60°C). The **TRETEC N** can be operated in a redundant way. It is possible to connect the device in series (max. 2 units) and in parallel up to 3 units without decoupling module. Due to its modern design it can be operated with a peak current in temperatures up to 45°C without load reduction.

2 Technical Data

Input	
Input	3 x 360 V ... 500 VAC $\pm 10\%$ 500 V ... 700 VDC $\pm 10\%$
Network	TN-S, TN-C, TT, IT grid
Nominal frequency	50 / 60 Hz $\pm 6\%$
Nominal current	0,75 A @ 3 x 360 V AC 0,55 A @ 3 x 500 V AC
Efficiency	93,7 %
No load power losses	2 W
Recommended pre-fusing max.	Max. 3 x 20 A (T) in house installation
Recommended circuit breaker	3 x 3...20 A characteristics C
Output	
Voltage	24 VDC $\pm 1\%$
Voltage adjustable	24-28 VDC / Potentiometer in front plate
Residual ripple	< 20 mV eff / rms
Output current max. 45°C	12,0 A
Derating at 60°C	10,0 A
at 70°C	7,0 A
Ride-through	> 25 ms
"Power Boost" current	15 A > 5 s without voltage drop
Short circuit current	after "Power Boost" follows constant current: 12 A
Switching in parallel	3 devices
Switching in series	2 devices
Connection input	
Terminal strip	4 x 6 mm ² with Push-In spring-type terminals
Connection output	
Terminal strip	4 x 2,5 mm ² with Push-In spring-type terminals

Technical Datasheet

TRETEC 2412N



J. Schneider
Elektrotechnik

Alarm contact	
Potential-free alarm contact for pre-warning at overload, overheating or short-circuit	30 V AC/DC 50 mA (ohmic)
Over voltage protection	yes
Terminal strip	2 x 2,5 mm ² Push-In spring-type terminals
Classification of environmental conditions	class 3K3 according to EN 60721
Relative humidity	95%, no condensation
Environmental temperature	-40 ... +70 °C see Derating
Storage temperature	-40 ... +85 °C
MTBF according to DIN EN 61709:1999-01, SN 29500, DIN EN ISO 13849-1:2008-12	> 1.000.000 h
Housing	
Dimensions	143 x 65 x 143 mm (H x W x D)
Weight	0,77 kg
Protection class	I
IP protection	IP 20
Degree of pollution	2
Fixation	Snap-on mounting on DIN rail
Installation direction	vertical
Material	metal

3 Norms and regulations

EN 61204-3
EN 61000-3-2/-3
EN 61000-4-2/-3/-4/-5/-6/-11
IEC / EN 60950-1
EN 60204-1
SEMI F47 – 0706
EN 60950-1 overvoltage categorie II
UL 508

CE-approval according to EMI standard 2014/30/EU and low voltage standard 2014/35/EU and EU standard 2011/65/EU (RoHS - standard) of the European Parliament and of the European Council from 8th of June 2011 for the limitation of the use of certain dangerous material in electrical and electronic devices (amended version).